

TM/AIO--MEDICAL DISPLAY ON MEDICAL CARTS



Key Specifications

- Display: 21.5" , 23.8" , 27" touchscreen
- Display Resolution: 1920 x 1080
- Viewing Angle: horizontal 89-degree, vertical 89-degree
- Number of Colors: 16.7M
- Brightness: 300 cd/m2 or more
- Response Time: 8 ms
- Speaker and Microphone: Built-in microphones and speakers
- Buttons: 1 x screen on/off button, 1 x menu button, 1 x auto/exit button, 2 x up/down buttons
- USB Port: 6 x USB 3.0
- USB Port for Touch Screen Connection: 1 x USB Type-B (2.0)
- USB Input Port: 1 x USB Type-B (3.0)
- HDMI: 1
- DC-In: 1
- Fan/Fanless: Fanless , with waterproof buttons
- AC/DC Adapter Input: 100 to 240V AC; Output: 19V DC, 3.78A
- Enclosure: ABS + PC plastics, antimicrobial enclosure
- Dimensions (H x W x D) approx : From suppliers ,411.8 x 639.1 x 45 mm
- Weight: ~ 8 kg
- VESA-compliant mounting: 100mm x 100mm VESA standard

- Regulatory/ Safety Certifications: ANSI/AAMI ES60601-1, IEC60601-1-2, FCC Part 18, FCC Part 15 Class B, IEC 62368-1, RCM, CCC
- Temperature Operation: 0°C to 40°C (32°F to 104°F); Storage: -10°C to 50°C (14°F to 122°F) Humidity 0% to 90% non-condensing



For full product
info and datasheet
[Click here](#)

Sphotoelec

Sphotoelec Co., Ltd, is a global provider of advanced touch and display solutions, ranging from resistive touch, projected capacitive touch, touch display modules, optical bonding service, touch monitors to all-in-one computer systems.

Sphotoelec